

Product Specifications

E10G22-T1-Mini

Synology

Hardware Specifications

General

Host Bus Interface	PCIe 3.0 ×2
Size (Height × Width × Depth)	26.37 mm x 45.38 mm x 75.7 mm
Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-20°C to 60°C (-5°F to 140°F)
Relative Humidity	5% to 95% RH
Warranty	3 Years
Notes	The warranty period starts from the purchase date as stated on your purchase receipt. (Learn more)

Network

IEEE Specification Compliance	• IEEE 802.3x Flow Control • IEEE 802.3u Fast Ethernet • IEEE 802.3ab Gigabit Ethernet • IEEE 802.3bz 2.5Gbps / 5Gbps Ethernet • IEEE 802.3an 10Gbps Ethernet
Data Transfer Rates	10 Gbps/5 Gbps/2.5 Gbps/1 Gbps/100 Mbps
Supported Features	• 9 KB Jumbo Frame • TCP/UDP/IP Checksum Offloading • Auto-negotiation between 100Mb/s, 1Gb/s, 2.5Gb/s, 5Gb/s, and 10Gb/s • TCP Segmentation Offload (TSO) • Large Send Offload (LSO) • Receive Side Scaling (RSS) • Generic Receive Offload (GRO) • Generic Segmentation Offload (GSO)

Compatibility

Applied Models

- DP series:DP340
- 25 series:DS1525+
- 23 series:DS923+, DS723+
- 22 series:RS422+, DS1522+

Notes

DSM version requirement: 7.1.1-42962 Update 4 or later version