

Product Specifications

E10G30-T1

Synology

Hardware Specifications

General

Host Bus Interface	PCIe 3.0 ×4
Bracket Height	Low Profile and Full Height
Size (Height × Width × Depth)	68.1 mm x 82 mm x 13 mm
Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-20°C to 60°C (-5°F to 140°F)
Relative Humidity	5% to 95% RH
Warranty	5 Years
Notes	The warranty period starts from the purchase date as stated on your purchase receipt. (Learn more)

Network

IEEE Specification Compliance	• IEEE 802.3x Flow Control • IEEE 802.3u Fast Ethernet • IEEE 802.3ab Gigabit Ethernet • IEEE 802.3bz 2.5Gbps / 5Gbps Ethernet • IEEE 802.3an 10Gbps Ethernet
Data Transfer Rates	10 Gbps/5 Gbps/2.5 Gbps/1 Gbps/100 Mbps
Supported Features	• 9 KB Jumbo Frame • TCP/UDP/IP Checksum Offloading • Receive Side Scaling (RSS) • Generic Receive Offload (GRO)

Compatibility

Applied Models

- FS series:FS6420, FS6400, FS3420, FS2500
- HD series:HD6500
- SA series:SA6400
- 26 series:RS6426xs+, RS4826xs+, RS3626xs, RS1626xs+, RS1226RP+, RS1226+, RS826RP+, RS826+
- 25 series:RS2825RP+, DS1825+
- 23 series:RS2423RP+II, RS2423RP+, RS2423+, DS1823xs+
- 22 series:RS822RP+, RS822+, DS2422+
- 21 series:RS2821RP+, RS2421RP+, RS2421+, RS1221RP+, RS1221+, DS1821+, DS1621+
- 20 series:RS820RP+, RS820+
- 19 series:DS2419+II, DS2419+, DS1819+
- 18 series:RS2818RP+, RS2418RP+, RS2418+

Notes

DSM version requirement: 7.1.1-42962 Update 5 or later version