

Product Specifications

E10G30-T2

Synology

Hardware Specifications

General	
Host Bus Interface	PCIe 3.0 ×8
Bracket Height	Low Profile and Full Height
Size (Height × Width × Depth)	68.9 mm x 167.7 mm x 14.7 mm
Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-20°C to 60°C (-5°F to 140°F)
Relative Humidity	5% to 95% RH
Warranty	5 Years
Notes	The warranty period starts from the purchase date as stated on your purchase receipt. (Learn more)

Network	
IEEE Specification Compliance	• IEEE 802.3x Flow Control • IEEE 802.3ad Link Aggregation • IEEE 802.3ab Gigabit Ethernet • IEEE 802.3an 10Gbps Ethernet
Data Transfer Rates	10 Gbps/1 Gbps
Supported Features	• TCP Segmentation Offload (TSO) • Receive Side Scaling (RSS) • Generic Segmentation Offload (GSO) • 1.5 - 9 KB Jumbo Frame • TCP/UDP Checksum Offload • Transmit side scaling (TSS) • SR-IOV • Large receive offload (LRO)

Compatibility

Applied Models

- PAS series: PAS7700
- FS series: FS6420, FS6400, FS3600, FS3420, FS3410, FS3400, FS2500
- HD series: HD6500
- SA series: SA6400, SA3610, SA3600, SA3410, SA3400D, SA3400, SA3200D
- UC series: UC3400, UC3200
- DP series: DP7400, DP7200
- 26 series: RS6426xs+, RS4826xs+, RS3626xs, RS1626xs+, RS1226RP+, RS1226+, RS826RP+, RS826+
- 25 series: RS2825RP+, DS1825+
- 23 series: RS2423RP+II, RS2423RP+, RS2423+, DS1823xs+
- 22 series: RS822RP+, RS822+, DS3622xs+, DS2422+
- 21 series: RS4021xs+, RS3621xs+, RS3621RPxs, RS2821RP+, RS2421RP+, RS2421+, RS1221RP+, RS1221+, DS1821+, DS1621xs+, DS1621+
- 20 series: RS820RP+, RS820+
- 19 series: RS1619xs+, DS2419+II, DS2419+, DS1819+
- 18 series: RS3618xs, RS2818RP+, RS2418RP+, RS2418+
- 17 series: RS4017xs+, RS3617xs+, RS3617RPxs, DS3617xsII, DS3617xs

Notes

DSM version requirement: 7.1.1-42962 Update 5 or later version