



S Series

TB9332-E (15 mm)

Thermal Bullet Network Camera



Technical Specifications

System Information

CPU	Multimedia SoC (System-on-Chip)
Flash	16 GB
RAM	1 GB

Camera Specifications

Image Sensor	Uncooled VOx Micro bolometer
Max. Resolution	Effective pixels: 640x512 Image scale up to: 1280x1024
Lens Type	Fixed-focal (Thermal lens)
Focal Length	f = 15 mm
Aperture	F1.0
Iris Type	Fixed Iris
Field of View	32.0° (Horizontal) 26.0° (Vertical)
Pan/Tilt/Zoom Functionalities	ePTZ: 4x digital zoom
Storage	MicroSD/SDHC/SDXC card slot (256GB capacity supported)
Pixel Size	12 μ m
Spectral Range	8 ~ 14 μ m
Sensitivity	NETD < 40 mK

Video

Compression	H.265, H.264
Maximum Frame Rate	25 fps @ 1280x1024

Maximum Streams	2 simultaneous streams
Main Stream	25 fps @ 1280x1024, 1280x720, 640x512
2nd Stream	25 fps @ 704x576, 352x240
Video Streaming	Adjustable resolution, CBR/VBR, Smart Encode
Image Settings	General settings video title and time stamp overlay, video orientation (flip, mirror, rotation)
	Thermal settings white balance, image adjustment (brightness, contrast, sharpness)
	Privacy mask Scheduled profile settings

Audio

Audio Capability	Two-way Audio
Compression	G.711, RAW_PCM
Interface	External microphone input External line output

Network

Users	Live viewing for up to 10 clients
Security	Access list, Password protection, User access log, User account management
Protocols	802.1X, DDNS, DHCP, DNS, FTP, HTTP, HTTPS, ICMP, IGMP, IPv4, IPv6, NTP, PPPoE, QoS, RTSP/RTP/RTCP, SMTP, TCP/IP, UDP, UPnP
Interface	10BASE-T/100BASE-TX Ethernet (RJ-45) *It is highly recommended to use standard CAT5e & CAT6 cables which are compliant with the 3P/ETL standard.
ONVIF	Profile G, S, T supported, specification available at www.onvif.org

AI Analytics

Compute Capability	SoC with built-in hardware deep learning accelerator (4T)
Applications	Temperature measurement alarms (difference, threshold, section, rise), Early Fire Detection (Fire spot detection, Smoking detection)
	VCA (Intrusion, Single line crossing, Double line crossing, Loitering, Wrong way, Enter, Leave)
	Support VCA alarms triggering by person, car, person or car; Support temperature alarms triggering by ignoring person, car, person or car

Solution Integration

Video Motion Detection	Smart motion detection
------------------------	------------------------

Alarm and Event

Event Trigger	Motion detection, I/O alarm, Disk alarm, VCA alarm, Temperature alarm
Event Action	Event notification via email, FTP, SD card, digital output, audio clip

General

Connectors	RJ-45 cable connector for 10/100 Mbps Network/PoE connection Audio input Audio output DC 12V power input AC 24V power input Digital input *2 Digital output *2 BNC RS-485
LED Indicator	System power and status indicator
Power Input	DC 12V, IEEE 802.3af PoE Class 2
Power Consumption	Max. 5W
Dimensions	141.8 (D) x 367.4 (H) mm
Weight	2350 g
Certifications	EMC CE (EN 55032, Class B), FCC (FCC Part 15 Subpart B), UKCA (BS EN 55032 Class B) Environment IP66
Operating Temperature	Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F)
Humidity	90% RH
Warranty	Up to 36 months

System Requirements

Operating System	Microsoft Windows 10/8/7 Mac 10.12 (Chrome only)
Web Browser	Chrome 58.0 or above Internet Explorer 10/11
Other Players	VLC: 1.1.11 or above

Temperature Measurement

Temperature Range	-20°C to 150°C (-4°F to 302°F)
Measurement Rule	Point, line, polygon (Up to 20 rules in total)
Temperature Alarm	Threshold alarm, Temperature difference alarm, Temperature rise alarm, Section alarm
Accuracy	± 2°C / ±2%

Included Accessories

Packing Contents	Quick installation guide, alignment sticker, waterproof accessory bag, screw pack, junction box, sunshield
------------------	--

VCA Detection Range

VCA Detection Distance (Human: 1.8x0.5m)	84m (275.6ft)
VCA Detection Distance (Vehicle: 4x1.5m)	190m (623.4ft)

Temperature Measurement

Object: 0.2x0.2m	50m (164ft)
------------------	-------------

Fire Detection	
Object: 1x1m	625m (2050ft)
Object: 0.2x0.2m	125m (410ft)
Smoking Detection	49m (160ft)

Johnson's Criteria (Thermal image)	
Human 1.8x0.5m	
Detection (1.5 pixels)	624m (2047ft)
Recognition (6 pixels)	156m (511ft)
Identification (12 pixels)	78m (255ft)

Vehicle 4x1.5m	
Detection (1.5 pixels)	1917m (6289ft)
Recognition (6 pixels)	479m (1571ft)
Identification (12 pixels)	239m (784ft)