



S Series

TT9333-E (3.5 mm)

Thermal Turret Network Camera



Technical Specifications

System Information

CPU	Multimedia SoC (System-on-Chip)
Flash	16 GB
RAM	1 GB

Camera Specifications

Image Sensor	Dual sensor: Uncooled VOx Micro bolometer + 1/2.7" Progressive CMOS
Max. Resolution	Thermal lens: 256x192 (image scale up to 704x576) / Optical lens: 2560x1440
Lens Type	Fixed-focal (Thermal lens) Fixed-focal (optical lens)
Focal Length	Thermal lens: f = 3.5 mm Optical lens: f = 4 mm
Aperture	Thermal lens: F1.0 optical lens: F1.6
Iris Type	Fixed Iris
Field of View	Thermal lens(3.5mm) 48.0° (Horizontal) 36.0° (Vertical) optical lens (4.0mm) 92.0° (Horizontal) 46.0° (Vertical)
Illuminators	Built-in IR Illuminator up to 35 meters; White light for strobe light warning
Pan/Tilt/Zoom Functionalities	ePTZ: 4x digital zoom
Storage	MicroSD/SDHC/SDXC card slot (256GB capacity supported)
Pixel Size	12 µm
Spectral Range	8 ~ 14 µm
Sensitivity	NETD < 50 mK

Video	
Compression	H.265, H.264, MJPEG
Maximum Frame Rate	Thermal: 25 fps @ 704x576 25 fps @ 2560x1440
Maximum Streams	2 simultaneous streams each sensor
Main Stream	Thermal: 25 fps @ 704x576 25 fps @ 2560x1440, 2304x1296, 1920x1080, 1280x720
2nd Stream	Thermal: 25 fps @ 704x576 25 fps @ 352x240, 256x192, 704x576, 640x480
Video Streaming	Adjustable resolution, CBR/VBR, Smart Encode
Image Settings	General settings video title and time stamp overlay, video orientation (flip, mirror, rotation) Thermal settings white balance, image adjustment (brightness, contrast, sharpness) Privacy mask Scheduled profile settings

Audio	
Audio Capability	Two-way Audio
Compression	G.711, RAW_PCM
Interface	Built-in microphone Built-in speaker External microphone input External line output

Network	
Users	Live viewing for up to 10 clients
Security	Access list, Password protection, User access log, User account management
Protocols	802.1X, DDNS, DHCP, DNS, FTP, HTTP, HTTPS, ICMP, IGMP, IPv4, IPv6, NTP, PPPoE, QoS, RTSP/RTP/RTCP, SMTP, TCP/IP, UDP, UPnP
Interface	10BASE-T/100BASE-TX Ethernet (RJ-45) *It is highly recommended to use standard CAT5e & CAT6 cables which are compliant with the 3P/ETL standard.
ONVIF	Profile G, S, T supported, specification available at www.onvif.org

AI Analytics	
Compute Capability	SoC with built-in hardware deep learning accelerator (1T)
Applications	Temperature measurement alarms (difference, threshold, section, rise), Early Fire Detection (Fire spot detection, Smoking detection, Smoke & flame detection) VCA (Intrusion, Single line crossing, Double line crossing, Loitering, Wrong way, Enter, Leave) Support VCA alarms triggering by person, car, person or car; Support temperature alarms triggering by ignoring person, car, person or car

Solution Integration	
Video Motion Detection	Smart motion detection

Alarm and Event	
Event Trigger	Motion detection, I/O alarm, Disk alarm, VCA alarm, Temperature alarm
Event Action	Event notification via email, FTP, SD card, digital output, audio clip; white light flashing and horn warning

General	
Connectors	RJ-45 cable connector for 10/100 Mbps Network/PoE connection Audio input Audio output DC 12V power input AC 24V power input Digital input *1 Digital output *1 RS-485
LED Indicator	System power and status indicator
Power Input	DC 12V, IEEE 802.3af PoE Class 3
Power Consumption	Max. 10W
Dimensions	140 (D) x 117.8 (H) mm
Weight	1040 g
Certifications	EMC CE (EN 55032, Class B), FCC (FCC Part 15 Subpart B), UKCA (BS EN 55032 Class B) Environment IP66
Operating Temperature	Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F)
Humidity	90% RH
Warranty	Up to 36 months

System Requirements	
Operating System	Microsoft Windows 10/8/7 Mac 10.12 (Chrome only)
Web Browser	Chrome 58.0 or above Internet Explorer 10/11
Other Players	VLC: 1.1.11 or above

Temperature Measurement	
Temperature Range	-20°C to 150°C (-4°F to 302°F)
Measurement Rule	Point, line, polygon (Up to 20 rules in total)
Temperature Alarm	Threshold alarm, Temperature difference alarm, Temperature rise alarm, Section alarm
Accuracy	± 2°C / ±2%

Included Accessories	
Packing Contents	Quick installation guide, alignment sticker, waterproof accessory bag, screw pack

VCA Detection Range	
VCA Detection Distance (Human: 1.8x0.5m)	30m (98.4ft)

VCA Detection Distance (Vehicle: 4x1.5m)	90m (295.3ft)
--	---------------

Temperature Measurement

Object: 0.2x0.2m	11.7m (38.4ft)
------------------	----------------

Fire Detection

Object: 1x1m	208m (682ft)
Object: 0.2x0.2m	41.7m (136ft)
Smoking Detection	13m (42ft)

Johnson's Criteria (Thermal image)

Human 1.8x0.5m

Detection (1.5 pixels)	146m (479ft)
Recognition (6 pixels)	36m (118ft)
Identification (12 pixels)	18m (59ft)

Vehicle 4x1.5m

Detection (1.5 pixels)	447m (1466ft)
Recognition (6 pixels)	112m (367ft)
Identification (12 pixels)	56m (183ft)